

LED5GX23/850

LED Plugin 2-Pin Replacement Lamps

SKU # 91410



SPECIFICATIONS

Efficacy 113 LPW Lumens 565 lm CCT 5000 K CRI 80 CRI DIMENSIONS MOL 6.7 in Diameter 0.39 in RATINGS & CERTIFICATIONS Safety Certifications ULus Location Ratings Damp	GENERAL	
Bib Base Type 523 Voltage 120 Wattage 5 W Wattage Replacement 13 Operating Life No0 hr Dimmable No Parading Temp Operating Temp 20 to 45 °C Warranty 13 Lystemart Efficacy 13 Lystemart Lumens 55 lystemart CCT 300 C Lystemart CRI 300 C Lystemart WATTON 6.7 in Diameter 1 3 Lystemart Selection Exterifications 1 3 Lystemart CCT 300 C Lystemart CRI 30 Lystemart Diameter 1 3 Lystemart Selection Exterifications 1 3 Lystemart Selection Ratings 1 3 Lystemart Exterifications 1 3 Lystemart Exterificat	UL Type	Туре А
Voltage 120 Wattage Replacement 5 % Operating Life 50,000 hr Dimmable No Operating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 113 LP Lumens 565 Im CCT 5000 k CRI 5000 k CRI 67 in Diameter 6.7 in Safety Certifications CULUs Location Ratings Joanp PACKAGING INFO 5	Bulb Shape	Plug-In
Wattage Replacement 5	Bulb Base Type	GX23
Wattage Replacement 13 Operating Life 50,000 hr Dimmable No Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 113 LPV Lumens 565 Im CCT 5000 k CRI 80 CRI PHOTOMETRIC CRI CRI 565 Im BOR	Voltage	120
Operating Life 50,000 hr Dimmable No Operating Temp 20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 113 LP Lumens 565 lm CCT 5000 k CRI 80 CRI PIMENSIONS ARTINGS CERTIFICATIONS Safety Certifications 0.39 lm Safety Certifications ULUs Location Ratings Damp PACKAGING INFO 5	Wattage	5 W
Dimmable No Operating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 113 LPW Lumens 565 Im CCT 5000 k CRI 80 CRI POMENSIONS MOL 67 Im Diameter 0.39 im Padety Certifications ULLus Safety Certifications ULLus Location Ratings Damp PACKAGING INFO 6	Wattage Replacement	13
Operating Temp -20 to 45 °C Warranty 5 year limited warranty PHOTOMETRIC Efficacy 113 LPW Lumens 565 lm CCT 5000 k CRI 80 CRI PHOMENSIONS MOL 6.7 in Diameter 0.39 in PAININGS & CERTIFICATIONS Safety Certifications CULlus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 6	Operating Life	50,000 hr
PHOTOMETRIC Efficacy 113 LPV Lumens 565 Im CCT 5000 K CRI 5000 K CRI 67 in Diameter 9 0.39 in FATINGS & CERTIFICATIONS Safety Certifications ULUs Location Ratings S PACKAGING INFO Standard Pack Quantity 6 FATINGS & Service Control of the	Dimmable	No
PHOTOMETRIC Efficacy	Operating Temp	-20 to 45 °C
Efficacy 113 LPW Lumens 565 lm CCT 5000 K CRI 80 CRI DIMENSIONS MOL 6.7 in Diameter 0.39 in CRATINGS & CERTIFICATIONS Safety Certifications ULUs Location Ratings Damp PACKAGING INFO Standard Pack Quantity 6	Warranty	5 year limited warranty
Lumens CCT CCT CRI BO CRI DIMENSIONS MOL Diameter MOL MOL Diameter MOL MOL MOL MOL MOL MOL MOL MO	PHOTOMETRIC	
CCT CRI S000 K CRI S0 CRI DIMENSIONS MOL 6.7 in Diameter 0.39 in RATINGS & CERTIFICATIONS Safety Certifications UULus Location Ratings UDAMP PACKAGING INFO Standard Pack Quantity 6	Efficacy	113 LPW
DIMENSIONS MOL 6.7 in Diameter 0.39 in RATINGS & CERTIFICATIONS Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 6	Lumens	565 lm
MOL 6.7 in Diameter 0.39 in RATINGS & CERTIFICATIONS Safety Certifications culture cu	ССТ	5000 K
MOL Diameter RATINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 6.7 in 6.7 in	CRI	80 CRI
PACKAGING INFO Standard Pack Quantity 0.39 in	DIMENSIONS	
RATINGS & CERTIFICATIONS Safety Certifications Location Ratings PACKAGING INFO Standard Pack Quantity 6 CULus Damp Damp	MOL	6.7 in
Safety Certifications CULus Location Ratings Damp PACKAGING INFO Standard Pack Quantity 6	Diameter	0.39 in
Location Ratings PACKAGING INFO Standard Pack Quantity Damp 6	RATINGS & CERTIFICATIONS	
PACKAGING INFO Standard Pack Quantity 6	Safety Certifications	cULus
Standard Pack Quantity 6	Location Ratings	Damp
	PACKAGING INFO	
UPC 043168914109	Standard Pack Quantity	6
	UPC	043168914109

 $\textbf{Source URL:} \ https://www.led.com/catalog/led-plugin-2-pin-replacement-lamps-91410$